



FOR GOOD REASONS

panDOMO[®] SP-MS

Satin-finish Sealer

Water-based, film-forming

Acrylate-Wax Protective Sealer

Satin finish

Anti-slip

Dirt-repellent

Hard-wearing

Tread-proof

Manufacturer with certified
QM/UM system in accordance with
DIN EN ISO 9001/14001

ARDEX GmbH
58430 Witten · P.O. Box 6120
GERMANY
Telephone: +49 (0) 23 02/664-0
Telefax: +49 (0) 23 02/664-437
kundendienst@ardex.de
www.ardex.de

panDOMO® SP-MS

Satin-finish Sealer

Areas of use:

For indoor use.

PANDOMO® SP-MS Satin-finish Sealer forms a protective coating on PANDOMO® floor systems that have been oiled with PANDOMO® SP-SL Stone Oil or PANDOMO® SP-PS Aqueous Polyurethane Sealer.

Floors that have been treated with PANDOMO® SP-SL Stone Oil must first be primed using PANDOMO® SP-F pore filler.

Properties:

- Anti-slip
- Coating provides short-term protection against liquids
- Tread-proof
- Satin finish

PANDOMO® SP-MS Satin-finish Sealer is dirt-repellent and lends treated floors a uniform, satin finish.

Application:

PANDOMO® SP-MS Satin-finish Sealer must only be applied on completely dry PANDOMO® SP-F pore filler (at least 4 hrs drying time at approx. +20°C) or to completely dry surfaces sealed with PANDOMO® SP-PS (at least 12 hrs drying time at approx. +20°C).

PANDOMO® SP-MS Satin-finish Sealer is applied undiluted using a lambskin wiper (squeegee-type) to create a thin, even coat.

The initial treatment consists of 2 coats. The waiting time between the first and the second coat will depend on drying conditions and will be approx. 60 minutes at room temperatures of approx. +20°C and a relative humidity of approx. 60 %. During application, the temperature of the air and the ground should be at least +15°C.

Do not wipe the partially dry surfaces again. Avoid ponding by wiping over area again immediately.

Notice:

Do not combine PANDOMO® SP-MS Satin-finish Sealer with other maintenance or cleaning products and do not use it for regular maintenance cleaning.

Do not walk on or wipe the floor as long as the protective coat still has a moist sheen.

Clean tools immediately after use with plenty of water.

Fine matting traces may be visible on dark PANDOMO® Floor surfaces after the first application.

Do not apply maximum loads until the stone oil or PU sealer is hard until approx. 5–7 days after initial treatment (depending on climate).

Maintenance cleaning:

Regular maintenance cleaning can be carried out using PANDOMO® SP-CR Maintenance and Repair Cleaner.

First remove dirt and sand using a broom or the brush side of a vacuum cleaner.

Dilute PANDOMO® SP-CR in the ratio of approx. 50 ml to 8 litres of water.

Wipe surfaces with damp not wet cloth and leave to dry. Do not wipe again with clear water. See Technical Data Sheet for further details.

Basic cleaning:

To remove stubborn dirt and stains that resist regular maintenance cleaning, we recommend a thorough deep cleaning. Use PANDOMO® SP-BC Basic Cleaner for this purpose. See Technical Data Sheet for details.

After deep-cleaning the floor with PANDOMO® SP-BC, it must be left to dry for a sufficiently long time. The floor must be completely dry before re-applying PANDOMO® SP-SL and PANDOMO® SP-MS. At least two coats of PANDOMO® SP-MS must be applied after a floor has been deep-cleaned.

General remarks:

The less the newly treated floor is used during the first few days, the longer it will last!

Notes on safety and waste disposal:

In case of contact with eyes: Rinse with water, including under eyelids.

In case of contact with skin: As a precaution, wash with plenty of water and soap.

If swallowed: Rinse mouth with water and drink plenty of water. Avoid vomiting if possible. If necessary, consult a doctor.

Conditions to be avoided: Do not expose to temperatures above +35°C.

Keep out of the reach of children.

Dispose of contents/containers in accordance with local/regional/national/international regulations.

**Technical data
based on ARDEX Quality Standards:**

Coverage:	25 ml/m ² per coat
Density	1.03 g/cm ³
pH value:	approx. 8.5
Appearance:	cloudy, whitish liquid
Solubility in water:	complete
Working temperature:	+15 – +25°C surface temperature, turn down or switch off floor heating in good time.
Drying time:	Dry to touch after approx. 30 minutes. Can be walked on carefully after approx. 2 hours. Full load-bearing capacity after 3 – 5 days. During this time, surfaces should only be cleaned with dry cloth or clear water. Low temperatures and high humidity will prolong the drying time.
Labelling according to GHS/CLP:	None
Labelling according to GGVSEB/ADR:	None
GISCODE:	GE10
Packaging:	5-litre plastic canister
Storage:	Store in cool but frost-proof surroundings, reseal containers tightly after opening.
Shelf life:	Can be stored for approx. 12 months in original unopened containers. After opening containers, use up contents as soon as possible.

