



PANDOMO® Protection Liquid

1K-PU Permanentcare

- silk matt
- dirt-repellent
- particularly hard-wearing and abrasion-resistant
- Preserves the mineral character
- Can be trafficked quickly
- Easy to apply



Field of application:

For interior use.

Polyurethane sealer for the permanent protection of PANDOMO® floors. Protects floor surfaces from fine scratches and traces of use with a care film.

Prevents premature wear and increases the service life of the surface.

Protective film for PANDOMO® floor systems oiled with PANDOMO® SP-SL Stone Oil, treated with PANDOMO® SP-PS Aqueous Polyurethane Sealer or treated exclusively with PANDOMO® SP-F Pore Filler.

Floor surfaces treated with PANDOMO® SP-SL Stone Oil must first be primed with PANDOMO® SP-F Pore Filler. (Floor surfaces previously sealed with PANDOMO® SP-PS do not require PANDOMO® SP-F Pore Filler prior to the application of PANDOMO® Protection Liquid).

Composition:

Water, polymers, water-soluble solvents, nonionic surfactants, preservatives

Application:

PANDOMO® Protection Liquid may only be applied to the cured PANDOMO® SP-F Pore Filler.

(min. 2 - 4 hours drying time at approx. +20°C) or on absolutely dry PANDOMO® SP-PS sealed surfaces (min. 12 hours drying time at approx. +20°C).

PANDOMO® Protection Liquid is applied undiluted in one layer, evenly and thinly as a wet film with a lambskin wiper (Wischwiesel).

Do not wipe into already drying product, this can lead to streaking. Avoid the formation of puddles. If a second coat is necessary, apply it the following day or after a drying time of at least 12 hours (at +20°C).

ARDEX GmbH
PO-Box 6120 · 58430 Witten
GERMANY
Tel.: +49 (0) 23 02/664-0
Fax: +49 (0) 23 02/664-240
technik@ardex.de
www.ardex.de

Manufacturer with QM/EM system
certified in accordance with
DIN EN ISO 9001/14001

PANDOMO® Protection Liquid

1K-PU Permanentcare

Hints:

To refresh existing PANDOMO® floor surfaces, first clean the surface from dust, dirt and loose particles. Then clean the surface damp with PANDOMO® Cleaner. Firmly adhering dirt and residues of old care products must first be removed by a basic cleaning with PANDOMO® Basic Cleaner. Please observe the respective Technical Data Sheets.

Do not walk on or wipe over the floor while the protective film is still shiny and damp.

Can be walked on after approx. 1 - 2 hours. Full loading capacity after approx. 12 hours.

If the surfaces need to be covered, this must be done after 12 hours at the earliest.

Maintenance cleaning:

For regular maintenance cleaning, use PANDOMO® Care & Clean or PANDOMO® Cleaner.

The respective product data sheets/PANDOMO® cleaning recommendations must be observed.

General:

The higher the overall film build-up, the higher the protective effect.

The more the freshly treated floor is protected in the first few days, the longer the life of the floor!

Safety-/disposal advice:

Keep out of the reach of children.

Contains reaction product of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May cause allergic reactions.

Safety data sheet available on request.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Technical data acc. To ARDEX-quality standard:

Material requirement: approx. 40 – 50 ml/m² (per coat)

Density: ca. 1,018 g/cm³

pH-value: ca. 8,4

Appearance: liquid-cloudy, milky

Application temperature: approx. + 15 - + 25°C
surface temperature
reduce or switch of
underfloor heating.

Drying time: Can be carefully walked on
after approx. 1 - 2 hours. Fully
loadable after approx. 12 hours.
Drying time between two
applications approx. 12 hours.

The times stated refer to
+ 20 °C and 50 % rH.

At low temperatures and high
humidity, the drying time will be
longer.

GISCODE: GE 10

Packaging: Canister with 5 L net

Storage: Store in a cool, but frost-proof
place, close opened containers
tightly

Storage time: Can be stored for approx. 24
months in the original sealed
container. Use opened containers
as soon as possible.